



Version: 3 Revision: 11.05.2016 Printing date: 11.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Muc-Off Disc Brake Cleaner

Article number: 913, 914, 916, 916H

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

Application of the substance / the mixture Cleaner solvent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Muc-Off Ltd. 1st Floor, Unit 1, Concept Office

Park, Innovation Close, Poole, Dorset

BH12 4QT, UK

Tel: +44 (0)1202 307790 Fax: +44 (0)1202 746853 E-mail: info@muc-off.com

- Further information obtainable from: Research & Development/E-mail: info@muc-off.com
- 1.4 Emergency telephone number: During normal opening hours: Tel +44 (0)1202 307790

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336

May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 1) · Precautionary statements If medical advice is needed, have product container or label at hand. P101 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. P251 P260 Do not breathe spray. P211 Do not spray on an open flame or other ignition source. P280 Wear protective gloves / eye protection. P271 Use only outdoors or in a well-ventilated area. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P403 Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Active substance with propellant

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	10-<25%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	1.0-<2.5%

· Ingredients according to detergents guidline 648/2004/EC	
aliphatic hydrocarbons	15 - 30%
	(Contd. on page 3)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

· Additional information:

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

 \cdot 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- & 1 Control parameters

• 8.1 Contro	ol parameters
· Ingredien	ts with limit values that require monitoring at the workplace:
64-17-5 et	thanol
WEL Lon	ng-term value: 1920 mg/m³, 1000 ppm
67-64-1 A	cetone
	ort-term value: 3620 mg/m³, 1500 ppm ng-term value: 1210 mg/m³, 500 ppm
106-97-8 k	butane (containing < 0.1% butadiene (203-450-8))
Lon	ort-term value: 1810 mg/m³, 750 ppm ng-term value: 1450 mg/m³, 600 ppm c (if more than 0.1% of buta-1.3-diene)
74-98-6 pi	ropane
	ort-term value: 3600 mg/m³, 2000 ppm ng-term value: 1800 mg/m³, 1000 ppm
107-98-2 1	1-methoxy-2-propanol
	ort-term value: 560 mg/m³, 150 ppm ng-term value: 375 mg/m³, 100 ppm
67-63-0 pi	ropan-2-ol
	ort-term value: 1250 mg/m³, 500 ppm ng-term value: 999 mg/m³, 400 ppm
123-86-4 r	n-butyl acetate
	ort-term value: 966 mg/m³, 200 ppm ng-term value: 724 mg/m³, 150 ppm
· DNELs	

67-64-1 Acetone

Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2420 mg/m3 (Worker)
	DNEL Long term-systemic	200 mg/m3 (Consumer)

(Contd. on page 5)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

				(Contd. of page 4)
			1210 mg/m3 (Worker)	
67-63-0 pi	ropan-2-ol			
Oral	DNEL Long term-s	ystemic	26 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-s	ystemic	319 mg/kg bw/day (Consumer)	
			888 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-s	ystemic	89 mg/m3 (Consumer)	
			500 mg/m3 (Worker)	
PNECs				
67-64-1 Acetone				
PNEC Ma	rine water	1.06 mg/l (Undefind)		
PNEC Fre	shwater sediment	30.4 mg/kg (Undefind)		
PNEC Soi	1	29.5 mg/kg (Undefind)		
PNEC Ma	rine water sediment	3.04 (Undefind)		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

(Contd. on page 6)

Version: 3 Revision: 11.05.2016 Printing date: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 5)

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information	on basic physical and chemical properties
· General Inform	ation
· Appearance:	

Form: Aerosol

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Undetermined. Melting point/Melting range: Boiling point/Boiling range: -44 °C

-97 °C · Flash point:

Not applicable. · Flammability (solid, gaseous):

365 °C · Ignition temperature:

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol % Upper: 20.0 Vol %

· Vapour pressure at 20 °C: 8300 hPa

· Density at 20 °C: 0.723 g/cm3 · Relative density Not determined. · Vapour density Not determined.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 6)

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 99.8 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

T T /T	050		4.0	• 6• 4 •
	('511 VOII	AC PALAVO	nt tar al	assification:
. 1/1//1	CSV Vail	ies i cieva	111 1171 (1	assiiicativii.

0. 0. 1110000		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	5800 mg/kg (rat) 7800 mg/kg (rbt) >20 mg/l (rat)
Inhalative	LC50/4h	>20 mg/l (rat)
(5 (3 0	2	1

67-63-0 propan-2-ol

67-64-1 Acetone

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m3 (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- $\cdot \ Serious \ eye \ damage/irritation$

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxici	ity:
67-64-1 Aceto	ne
EC50	8800 mg/l (Daphnia magna)

(Contd. on page 8)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 7)

| 8300 (96h) mg/l (Fish)
| 67-63-0 propan-2-ol |
| LOEC (8 days) | 1000 mg/l (algae) |
| LC50/96h | 9640 mg/l (Pimephales promelas) |
| LC50 (24h) | 9714 mg/l (Daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, ADN, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR, ADN UN1950 AEROSOLS
- · IMDG AEROSOLS
- · IATA AEROSOLS, flammable
- · 14.3 Transport hazard class(es)
- · ADR



- · Class 2 5F Gases.
- · Label 2.1
- \cdot ADN
- · ADN/R Class: 2 5F
- · IMDG, IATA



- · Class 2.1
- · Label 2.1

(Contd. on page 9)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
• 14.6 Special precautions for user • Danger code (Kemler): • EMS Number: • Stowage Code • Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from"
· 14.7 Transport in bulk according to Anno Marpol and the IBC Code	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. ex II of Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 28, 29
- · National regulations:

Class	Share in %
NK	75-<100

- · **VOC-CH** 99.84 %
- · VOC-EU 721.8 g/l
- · Danish MAL Code 3-1

(Contd. on page 10)

Printing date: 11.05.2016 Version: 3 Revision: 11.05.2016

Trade name: Muc-Off Disc Brake Cleaner

(Contd. of page 9)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

SVHC: Substances of Very High Concern

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB